



Fortinet

FCSS_SASE_AD-24 Exam

FCSS - FortiSASE 24 Administrator

Thank you for Downloading FCSS_SASE_AD-24 exam PDF Demo

You can also try our FCSS_SASE_AD-24 practice exam software

Download Free Demo

https://prepbolt.com/FCSS_SASE_AD-24.html

QUESTIONS & ANSWERS

DEMO VERSION

(LIMITED CONTENT)

Version: 4.0

Question: 1

Refer to the exhibits.

Web Filtering logs

	User	Destination P...	Traffic Type	Security Events	Security Action	Log Details
<input checked="" type="checkbox"/>	user2@fortinettraining.lab	443	Internet Access	Web Filter	Allowed	<div style="border: 1px solid #ccc; padding: 5px;"> <div style="display: flex; justify-content: space-between; border-bottom: 1px solid #ccc;"> Details Security </div> <p>Agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/122.0.0.0 Safari/537.36</p> <p>Category: 50</p> <p>Category Description: Information and Computer Security</p> <p>Direction: outgoing</p> <p>Event Type: ftgd_allow</p> <p>Hostname: www.eicar.org</p> <p>Message: URL belongs to an allowed category in policy</p> <p>Profile Group: SIA (Internet Access)</p> <p>Referrer URI: https://www.eicar.org/download-anti-malware-testfile/</p> <p>Request Type: referral</p> <p>Sub Type: webfilter</p> <p>Type: utm</p> <p>Timezone: -0800</p> <p>URL: https://www.eicar.org/download/eicar_com-zip/?vpmid=8847&refresh=65df3477aha001709126775</p> </div>
<input type="checkbox"/>	user2@fortinettraining.lab	443	Internet Access	Web Filter	Allowed	
<input type="checkbox"/>	user2@fortinettraining.lab	443	Internet Access	Web Filter	Allowed	
<input type="checkbox"/>	user2@fortinettraining.lab	443	Internet Access	Web Filter	Allowed	
<input type="checkbox"/>	user2@fortinettraining.lab	443	Internet Access	Web Filter	Allowed	
<input type="checkbox"/>	user2@fortinettraining.lab	443	Internet Access	Web Filter	Allowed	
<input type="checkbox"/>	user2@fortinettraining.lab	443	Internet Access	Web Filter	Allowed	
<input type="checkbox"/>	user2@fortinettraining.lab	443	Internet Access	Web Filter	Allowed	
<input type="checkbox"/>	user2@fortinettraining.lab	443	Internet Access	Web Filter	Allowed	
<input type="checkbox"/>	user2@fortinettraining.lab	443	Internet Access	Web Filter	Allowed	
<input type="checkbox"/>	user2@fortinettraining.lab	443	Internet Access	Web Filter	Allowed	
<input type="checkbox"/>	user2@fortinettraining.lab	443	Internet Access	Web Filter	Allowed	
<input type="checkbox"/>	user2@fortinettraining.lab	443	Internet Access	Web Filter	Allowed	
<input type="checkbox"/>	user2@fortinettraining.lab	443	Internet Access	Web Filter	Allowed	

Security Profile Group

Rename
 Delete

AntiVirus

Threats	Count	Inspected Protocols
		HTTP ✔
		SMTP ✔
		POP3 ✔
		IMAP ✔
		FTP ✔
		CIFS ✔

View All
 View Logs
 Customize

Web Filter With Inline-CASB

Threats	Count	Filters	
www.eicar.org	150	✔ Allow	0
5f3c395.com19.de	22	✘ Block	0
www.eicar.com	13	⊖ Exempt	0
encrypted-tbn0.gstatic.com	5	👁 Monitor	93
ocsp.digicert.com	4	⚠ Warning	0
		✘ Disable	0
		🔒 Inline-CASB Headers	1

View All
 View Logs
 Customize

Intrusion Prevention

Threats	Count	Intrusion Prevention
		<div style="border: 1px solid #ccc; padding: 5px; margin-bottom: 5px;"> Recommended ✘ Scanning traffic for all known threats and applying the recommended settings. </div> <div style="border: 1px solid #ccc; padding: 5px; display: inline-block;"> ⏸ Disabled </div>

View All
 View Logs
 Customize

SSL Inspection

Threats	Count	SSL Inspection
ssl-anomaly	734	Deep Inspection 📘 SSL connections are decrypted to allow for inspection of the contents.
		🔒 Exempt Hosts 1
		🔒 Exempt URL Categories 2

View All
 View Logs
 Customize

Secure Internet Access policy

The screenshot shows the configuration for a Secure Internet Access policy named "Web Traffic". The configuration is as follows:

- Name:** Web Traffic
- Source Scope:** VPN Users (selected), All, Edge Device
- Source:** All Traffic (selected), Specify
- User:** All VPN Users, Specify
 - VPN_Users (selected)
- Destination:** All Internet Traffic (selected), Specify
- Service:** ALL (selected)
- Profile Group:** Default, Specify
 - SIA (selected)
- Force Certificate Inspection:** Enabled (toggle)
- Action:** Accept (selected), Deny
- Status:** Enable (selected), Disable
- Logging Options:**
 - Log Allowed Traffic: Enabled (toggle)
 - Security Events (selected), All Sessions

A FortiSASE administrator has configured an antivirus profile in the security profile group and applied it to the internet access policy. Remote users are still able to download the eicar.com-zip file from <https://eicar.org>. Traffic logs show traffic is allowed by the policy.

Which configuration on FortiSASE is allowing users to perform the download?

- A. Web filter is allowing the traffic.
- B. IPS is disabled in the security profile group.
- C. The HTTPS protocol is not enabled in the antivirus profile.
- D. Force certificate inspection is enabled in the policy.

Answer: D

Explanation:

<https://community.fortinet.com/t5/FortiSASE/Technical-Tip-Force-Certificate-Inspection-option-in-FortiSASE/ta-p/302617>

Question: 2

An organization wants to block all video and audio application traffic but grant access to videos from CNN Which application override action must you configure in the Application Control with Inline-CASB?

- A. Allow
- B. Pass
- C. Permit
- D. Exempt

Answer: A


Explanation:

<https://docs.fortinet.com/document/fortisase/24.4.75/sia-agent-based-deployment-guide/568255/configuring-application-control-profile>

Question: 3

Refer to the exhibits.

Topology



Priority settings

<input type="checkbox"/>	Name	Priority
<input type="checkbox"/>	HUB-1	P1 <input type="text" value=""/> (Highest Priority)
<input type="checkbox"/>	HUB-2	P2 <input type="text" value=""/>

When remote users connected to FortiSASE require access to internal resources on Branch-2. how will traffic be routed?

- A. FortiSASE will use the SD-WAN capability and determine that traffic will be directed to HUB-2. which will then route traffic to Branch-2.
- B. FortiSASE will use the AD VPN protocol and determine that traffic will be directed to Branch-2 directly, using a static route
- C. FortiSASE will use the SD-WAN capability and determine that traffic will be directed to HUB-1, which will then route traffic to Branch-2.
- D. FortiSASE will use the AD VPN protocol and determine that traffic will be directed to Branch-2 directly, using a dynamic route

Answer: D

Explanation:

Question: 4

What are two advantages of using zero-trust tags? (Choose two.)

- A. Zero-trust tags can be used to allow or deny access to network resources
- B. Zero-trust tags can determine the security posture of an endpoint.
- C. Zero-trust tags can be used to create multiple endpoint profiles which can be applied to different endpoints
- D. Zero-trust tags can be used to allow secure web gateway (SWG) access

Answer: AB

Explanation:

Zero-trust tags are critical in implementing zero-trust network access (ZTNA) policies. Here are the two key advantages of using zero-trust tags:

Access Control (Allow or Deny):

Zero-trust tags can be used to define policies that either allow or deny access to specific network resources based on the tag associated with the user or device.

This granular control ensures that only authorized users or devices with the appropriate tags can

access sensitive resources, thereby enhancing security.

Determining Security Posture:

Zero-trust tags can be utilized to assess and determine the security posture of an endpoint.

Based on the assigned tags, FortiSASE can evaluate the device's compliance with security policies, such as antivirus status, patch levels, and configuration settings.

Devices that do not meet the required security posture can be restricted from accessing the network or given limited access.

Reference:

FortiOS 7.2 Administration Guide: Provides detailed information on configuring and using zero-trust tags for access control and security posture assessment.

FortiSASE 23.2 Documentation: Explains how zero-trust tags are implemented and used within the FortiSASE environment for enhancing security and compliance.

Question: 5

Refer to the exhibit.



In the user connection monitor, the FortiSASE administrator notices the user name is showing random characters. Which configuration change must the administrator make to get proper user information?

- A. Turn off log anonymization on FortiSASE.
- B. Add more endpoint licenses on FortiSASE.
- C. Configure the username using FortiSASE naming convention.
- D. Change the deployment type from SWG to VPN.

Answer: A

Explanation:

In the user connection monitor, the random characters shown for the username indicate that log anonymization is enabled. Log anonymization is a feature that hides the actual user information in the logs for privacy and security reasons. To display proper user information, you need to disable log anonymization.

Log Anonymization:

When log anonymization is turned on, the actual usernames are replaced with random characters to protect user privacy.

This feature can be beneficial in certain environments but can cause issues when detailed user monitoring is required.

Disabling Log Anonymization:

Navigate to the FortiSASE settings.

Locate the log settings section.

Disable the log anonymization feature to ensure that actual usernames are displayed in the logs and

user connection monitors.

Reference:

FortiSASE 23.2 Documentation: Provides detailed steps on enabling and disabling log anonymization.

Fortinet Knowledge Base: Explains the impact of log anonymization on user monitoring and logging.

Thank You for trying FCSS_SASE_AD-24 PDF Demo

To try our FCSS_SASE_AD-24 practice exam software visit link
below

https://prepbolt.com/FCSS_SASE_AD-24.html

Start Your FCSS_SASE_AD-24 Preparation

Use Coupon "SAVE50" for extra 50% discount on the purchase of
Practice Test Software. Test your FCSS_SASE_AD-24 preparation
with actual exam questions.

