



IBM AIX v7 Administrator Specialty

Thank you for Downloading S1000-007 exam PDF Demo

You can also try our S1000-007 practice exam software

### **Download Free Demo**

https://prepbolt.com/S1000-007.html

# QUESTIONS & ANSWERS DEMOVERSION (LIMITED CONTENT)

## Version: 4.1

#### Question: 1

What are three states a device can have when connected to an AIX system?

- A. Available
- B. Defined
- C. Stopped
- D. Blocked
- E. Running
- F. Suspended

Answer: ABC

Explanation:

Devices that are connected to the system can be in one of four states.

Devices that are connected to the system can be in one of the following states:

Item Description

Undefined The device is unknown to the system.

Defined Specific information about the device is recorded in the customized database, but it is unavailable to the Available A defined device is coupled to the operating system, or the defined device is configured.

Stopped The device is unavailable but remains known by its device driver.

If a tty device and a printer alternately use the same tty connector, both a tty device and a printer are defined on the same parent and port in the device configuration database. Only one of these devices can be configured at a time. When the tty connector is configured, the printer specific setup information is retained until it is configured again. The device is not removed; it is in the defined state. Maintaining a device in defined state retains customized information for a device that is not currently in use, either before it is first made available or while it is temporarily removed from the system.

If a device driver exists for a device, the device can be made available through the device driver. <u>https://www.ibm.com/docs/en/aix/7.2?topic=nodes-device-states</u>

PrepBolt.com

#### Question: 2

What command is used to monitor SAN I/O performance/throughput?

A. iostat -DIRT 60 10 B. mpstat -w 1 C. ioo -L D. vmstat -i 1

Answer: A

Explanation:

The command used to monitor SAN I/O performance/throughput is iostat -DIRT 60 10. The iostat command is used to monitor I/O performance and throughput on a SAN device. The DIRT (Disk I/O Response Time) flag can be used to display the response time for each I/O request. The last two arguments, 60 and 10, are the interval (in seconds) and the number of iterations respectively. This command will monitor I/O performance/throughput every 60 seconds for 10 iterations.

#### Question: 3

An IT security department would like to limit root user access to only members of the group called system. Which command will accomplish this?

- A. chgroup admin=root system
- B. cruiser sugroups=system root
- C. chadmin user=root system
- D. chadmin group=system root

Answer: D

Explanation:

The "chadmin" command can be used to modify the attributes of a user account, including the groups that the user belongs to. The syntax for limiting root user access to members of the group called "system" would be:

sql

chadmin group=system root

This command will add the root user to the "system" group and remove it from any other groups. Members of the "system" group will be the only ones able to access the root account.

#### Question: 4

Which statement is true regarding the snap command?

A. It collects performance related data.

B. By default, it will check there is enough space where the data is to be stored.

- C. C. All options are enabled by default.
- D. The data must be stored in /tmp.

Answer: B

Explanation:

"The command to limit root user access to only members of the group called system is chadmin group=system root. This command will set the primary group of the root user to the system group, thereby limiting root user access to only members of that group. This command can be used to set any user's primary group, not just root." The source of this information is the IBM AIX v7 Administrator Specialty Study Guide.

#### Question: 5

#### PrepBolt.com

An AIX administrator installed the fileset named useful\_fileset. How can they determine which files are included in the fileset?

A. file -f useful\_\_fileset B. lslpp -f useful\_fileset C. rpm -qf useful\_fileset D. lppchk -f useful fileset

Answer: B

Explanation:

The "lslpp" command can be used to display information about filesets installed on an AIX system. To determine which files are included in the "useful\_fileset" fileset, the administrator can run the following command:

lslpp -f useful\_fileset

This command will display detailed information about the "useful\_fileset" fileset, including a list of the files that are included in the fileset. This information can be useful for verifying the installation of the fileset and for troubleshooting problems that may be related to the fileset.

#### PrepBolt.com

## Thank You for trying S1000-007 PDF Demo

To try our S1000-007 practice exam software visit link below

https://prepbolt.com/S1000-007.html

## Start Your S1000-007 Preparation

Use Coupon "SAVE50" for extra 50% discount on the purchase of Practice Test Software. Test your S1000-007 preparation with actual exam questions.

PrepBolt.com